




**MULTIPHASE  
POWER**

Diesel Generator Set

# MPL400C

Powered By Cummins

50 Hz / 1500 RPM



**MULTIPHASE CORPORATION CO., LTD.**

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,  
Kwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310

Tel: +66 02 168 3193-5 #109 Fax: +66 02 168 3192

Email: [marketing@multiphase-corp.com](mailto:marketing@multiphase-corp.com) Website: [www.multiphase-power.com](http://www.multiphase-power.com)

Facebook: [www.facebook.com/MultiphasePower](http://www.facebook.com/MultiphasePower) Line ID: @multiphasepower



# MPL400C



MODEL	FREQUENCY / RPM	STANDBY POWER	PRIME POWER
MPL400C Powered by Cummins	50 Hz/1500 RPM	400 kVA	350 kVA
		320 kW	280 kW

- Model : MPLxxCS – S Suffix for silent type

General Technical Data	
Model	MPL400C
Engine	Cummins NTAA855-G7
Standard Voltage	400/230V
Phase	3 Phase
Stamford Alternator	HCI444E or S4L1D-E41
Leroy Somer Alternator	LSA46.3L11 or TAL-A46-H
Other Alternator	n/a
Speed Control Type	Electronic
Controller Model	DSE7320
Generator Set Fuel Consumption (L/hr)	
Load-Standby Power (110%)	94.0
Load-Prime Power (100%)	85.4
Load-Prime Power (75%)	64.7
Load-Prime Power (50%)	44.6

Multiphase Power Generators are in conformity with certification ISO 9001/ ISO14001/ISO18001 and our gensets are compliant with CE Standard. Best quality of electricity, high starting and loading capacity according to ISO8528-5. Ambient conditions of reference according to ISO 8528-1:2018 normative: 1000 mbar, 25°C, 30% relative humidity.

#### Prime Power (PRP):

According to ISO 8528-1:2018, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24 h of operation shall not exceed 70 % of the PRP.

#### Emergency Standby Power (ESP):

According to ISO 8528-1:2018, Emergency standby power is the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 h of operation per year with the maintenance intervals and procedures being carried out as prescribed by the manufacturers. The permissible average power output over 24 h of operation shall not exceed 70 % of the ESP

#### Continuous Power (COP):

According to Standard ISO 8528-1:2018, this is the maximum power available for continuous loads for unlimited running hours a year between the maintenance times recommended by the manufacturer under the environmental conditions established by the same.

Generator Set Ratings						
Voltage	Phase	Standby Rating			Prime Rating	
		KVA	KW	AMPS	KVA	KW
415/240v	3	400	320	556.5	350	280
400/230v	3	400	320	577.4	350	280
380/220v	3	400	320	607.8	350	280

#### Operating Environmental Requirement

- Abmient Temperature: -25°C - 50°C (Heater must be included when in low temperature)
- Himidity: Less than 80%
- Altitude: Up to 1000meters (For higher altitude application, please consult with Our Team)

#### MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,  
Kwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310 Tel: +66 02 168 3193-5  
Website: www.multiphase-power.com Line ID: @multiphasepower

## DIMENSIONS

Weight And Dimensions	Open Type	Silent Type
Length (mm)	3270	4350
Width (mm)	1230	1500
Height (mm)	2020	2260
Net Weight (kg)	2940	4350
Fuel Tank Capacity (L)	640	800
Running Hours - 100% Load	7.5	9.4



## DIESEL ENGINE SPECIFICATION

<b>Manufacturer</b>	Cummins	<b>Engine Design</b>	<b>Standby Power</b>	<b>Prime Power</b>
<b>Engine Model</b>	NTAA855-G7	<b>Engine Idle Speed (rpm)</b>	575-650	575-650
<b>Cylinders No./Arrangement</b>	6 / In-Line	<b>Gross Engine Output (KW)</b>	377	343
<b>Compression Ratio</b>	14.0:1	<b>Piston Speed (m/s)</b>	7.62	7.62
<b>Injection Type</b>	Direct	<b>Engine Water Flow (L/min)</b>	5	5
<b>Aspiration Type</b>	Turbocharged & Air-Air Cooled	<b>Intake Air Flow (L/s)</b>	485	510
<b>134</b>	140x152 mm	<b>Exhaust Gas Flow (L/s)</b>	1090	1150
<b>Displacement</b>	14 L	<b>Exhaust Gas Temp (°C)</b>	497	451

### MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,  
Kwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310 Tel: +66 02 168 3193-5  
Website: www.multiphase-power.com Line ID: @multiphasepower



Diesel Engine Specifications		
Air Intake System	Max. Intake Air Restriction with Heavy Duty Air Cleaner	
	Dirty Element (kPa)	6.22
	Clean Element (kPa)	3.74
Lubrication System	Engine Oil Pressure for Engine Protection Devices	
	Idle Speed (Minimum) (kPa)	103
	Governed Speed (kPa)	241-345
	Max. Allowable Oil Temperature (°C)	121
	Total system capacity (L)	38.6
Fuel System	Type Injection System	Direct Injection Cummins PT
	With Clean Fuel Filter (kPa)	13.5
	With Dirty Fuel Filter (kPa)	27.1
	Max. Fuel Temperature (°C)	71
Cooling System	Coolant Capacity - Engine Only (L)	20.8
	Max. Coolant Friction Head External to Engine - (kPa)	41
	Max. Coolant Pressure (kPa)	276
	Standard Thermostat (Modulating) Range (°C)	82-94
	Min. Allowable Pressure Cap (kPa)	48.2
	Max. Coolant Temperature (°C)	96
Electrical System	Minimum Recommended Battery Capacity (V)	24
	Cold Soak CCA	900
	Minimum Reserved Capacity - CCA	320
Exhaust System	Max. Back Pressure (kPa)	10

## ALTERNATOR SPECIFICATION

Poles	4
Insulation	Class H
Protection Rating	IP23
Exciter System	Self-Excited, Brushless
AVR Regulation Range	±1%
Number Of Bearing	Single Bearing
Coupling System	Flexible Disc
Winding Pitch	2/3
Overspeed Protection	2250 R.P.M.

### ALTERNATOR STANDARD FEATURES

- All models are brushless, rotating-field alternators
- Alternator meet the main international standard of IEC 60034, NEMA MG 1.32-33, BS 5000 Part 99, VDE 0530, ISO 8528/3
- The AVR voltage regulator provides superior short circuit capability
- Self-ventilated and dip proof construction
- Superior voltage waveform

Note: See Alternator Data Sheets for application data and ratings, efficiency curves, voltage dip with motor starting curves, and short circuit decrement curves

### MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,  
Kwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310 Tel: +66 02 168 3193-5  
Website: www.multiphase-power.com Line ID: @multiphasepower

## CONTROL SYSTEM DATA (DSE7320)



### Main Feature

The DSE7320 will also monitor the mains (utility) supply. The modules include USB, RS232 and RS485 ports as well as dedicated DSENet® terminals for system expansion.

### Key Function

- 4-Line back-lit LCD text display
- Five key menu navigation
- Front panel editing with PIN protection
- Customisable status screens
- Power save mode
- Support for up to three remote display units
- 9 configurable inputs
- 8 configurable outputs
- Flexible sender inputs
- Configurable timers and alarms
- 3 configurable maintenance alarms
- Multiple date and time scheduler
- Configurable event log (250)
- Integral PLC editor
- Easy access diagnostic page
- CAN and Magnetic Pick-up/Alt. sensing
- Fuel usage monitor and low fuel alarms
- Charge alternator failure alarm
- Manual speed control (on compatible CAN engines)
- Manual fuel pump control
- Power monitoring (kWh, kVAr, kVAh, kVArh)
- Load switching (load shedding and dummy load outputs)
- Automatic load transfer (DSE7320)
- Backed up real time clock
- Start & stop capability via SMS messaging
- USB connectivity
- Tier 4 CAN engine support
- DSENet ® expansion compatible etc.

### MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,  
Kwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310 Tel: +66 02 168 3193-5  
Website: www.multiphase-power.com Line ID: @multiphasepower

## OPTIONAL

Genset Optional Specifications	
Engine	Water Jacket Pre-Heater
	Oil Pre-Heater
	Fuel-Water Separator
Alternator	Winding and Bearing Temperature Detector (RTD)
	Anti-Condensation Heater (Space Heater)
	PMG / AREP
	Anti-Damp and Anti-Corrosion Treatment
Electrical System	ATS
	Remote Control and Monitoring
	Synchronizing System
	3/5 Pin sockets with RCBO protection
Fuel System	Bunded Double Wall Base Fuel Tank
	Extended To Larger Capacity Base Tank
	Free-stand Daily Fuel Tank
	Automatic Fuel Feeding System
	Fuel T-valves
Canopy	Trailer
	Rental Type Design

Optional Controller Model	
ComAp Controller for Single Genset Application	ComAp Nano MRS3
	ComAp AMF20
	ComAp AMF25
ComAp Controller for Multi Genset Application	ComAp IG200
	ComAp IG-NT
Deepsea Controller for Single Genset Application	DSE4520 MKII
	DSE6020 MKII
	DSE7320 MKII /DSE7420MKII
Deepsea Controller for Multi Genset Application	DSE8610 MKII
	DSE8810 MKII

### MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,  
Kwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310 Tel: +66 02 168 3193-5  
Website: www.multiphase-power.com Line ID: @multiphasepower