




**MULTIPHASE  
POWER**

Diesel Generator Set

# MPY250SC

Powered By SDEC

50 Hz / 1500 RPM



**MULTIPHASE CORPORATION CO., LTD.**

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,  
Khwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310  
Tel. : +66 02 168 3193-5 Fax. : +66 02 168 3192

Email : [marketing@multiphase-corp.com](mailto:marketing@multiphase-corp.com) Website : [www.multiphase-power.com](http://www.multiphase-power.com)  
Facebook : [www.facebook.com/MultiphasePower](http://www.facebook.com/MultiphasePower) Line ID : @multiphasepower



# MPY250SC



MODEL	FREQUENCY / RPM	STANDBY POWER	PRIME POWER
MPY250SC Powered by SDEC	50 Hz/1500 RPM	200 kW	180 kW
		250 kVA	225 kVA


- Available for voltages 400/230V, 480/277V, 380/220V, 440/254V, 416/240V, 220/127V, 208/120V
- All datas based on ISO 3046, altitude 100m (328ft), barometric pressure 100kPa (29.53 inHg), air temperature 25 °C (77 °F), relative humidity 30%.
- Diesel generators comply with standards : ISO8528, ISO14000, ISO3046, GB755, BS5000, VDE0530, IEC34-1
- Model : MPYxxCS – S Suffer for silent type

## GENERAL CHARACTERISTICS

Model	MPY250SC
Engine	SDEC SC9D310D2
Alternator	Leroy Somer TAL-A46-D
Voltage (V)	400/230
Current (A)	325
Connection	3 Phase, 4W/Y
Frequency	50 Hz
Engine Speed (RPM)	1500
Rated Power Factor	0.8
Controller Model	DSE7320

## DIMENSIONS

DIMENSIONS	OPEN TYPE	SILENT TYPE
Length (L)	2550 mm	3000 mm
Width (W)	1100 mm	1200 mm
Height (H)	1660 mm	1800 mm
Net Weight (KG)	1670 kg	2270 kg



### MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,  
Khwaeng Huai Khwang, Khet Huai Khwang, Bangkok, 10310 Tel. : +66 02 168 3193-5  
Website : [www.multiphase-power.com](http://www.multiphase-power.com) Line ID : @multiphasepower

## STANDARD CONFIGURATION

Engine	SDEC, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.
Alternator	LEROY SOMER brushless AC alternator
Radiator	Silent Type 50 °C (Open Type 40 °C), fan protective shroud
Base Frame	≤ 550 KW : base mounted fuel tank, anti-vibration pads, battery holder > 550 KW : channel steel base frame, anti-vibration pads, battery holder
Circuit Breaker	> 63A ≤1250A : Molded case circuit breaker (MCCB)
Control System	DEEP SEA 7320
Start Battery	Dry charged battery, available for 6 times starts under standard condition; connection cables.
Installation Accessories	Bellow, Elbow and Flange, Exhaust Silencer, etc.
Documents	Electric drawing, Operation & Maintenance Manual, Certification etc.

## OPTIONAL CONFIGURATION

Engine Accessories	<ul style="list-style-type: none"> <li>• Heavy-Duty Air Filter</li> <li>• Coolant Heater</li> <li>• Lube Oil Heater</li> <li>• Fuel and Water Separator</li> </ul>
Alternator and Accessories	<ul style="list-style-type: none"> <li>• Stamford or Leroy Somer or Others</li> </ul>
Cooling System	<ul style="list-style-type: none"> <li>• High Voltage ___ kV</li> <li>• 50 °C Radiator</li> <li>• Heat Exchanger + Water Cooling Tower + External Water Circulation Pumping System</li> <li>• Remote Horizontal Water Tank System</li> </ul>
Control System	<ul style="list-style-type: none"> <li>• AMF</li> <li>• Parallel</li> <li>• Practical Type in Low Temperature Environment</li> <li>• Control Screen Heater</li> <li>• Other</li> </ul>
Circuit Breaker	<ul style="list-style-type: none"> <li>• ¾ Poles</li> <li>• Fixed/Handcart Type</li> <li>• Electric Mechanism</li> </ul>
Automatic Transfer Switch	<ul style="list-style-type: none"> <li>• ATS Cabinet</li> </ul>
Start Battery	<ul style="list-style-type: none"> <li>• Nickel-Cadmium Battery</li> <li>• Maintenance-Free Battery</li> <li>• Power Charger and Selector</li> <li>• Charging Current Meter</li> </ul>
External Fuel Tank	<ul style="list-style-type: none"> <li>• 500 L, 1000 L, 1500 L, 2000 L, 2500L, 3000L, 4000L, 5000L</li> </ul>

### MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,  
Khwaeng Huai Khwang, Khet Huai Khwang, Bangkok, 10310 Tel. : +66 02 168 3193-5  
Website : www.multiphase-power.com Line ID : @multiphasepower

## ENGINE DATA

Engine Model	SDEC SC9D310D2
Engine Power	228 kW.
Aspiration	Water-cooled, Turbocharged air-to-air intercooled
Displacement (L)	8.82
Type	In-Line
Bore x Stroke (mm)	114 x 144
No. of Cylinders	6
Compression Ratio	18 : 1
Governor Type	Electric Governor
Rated Speed (RPM)	1500
Prime Power Fuel Consumption (L/h)	50.6
Standby Power Fuel Consumption (L/h)	55.6
Fuel	Sumer: GB 252-2000 top ASTM D975 No.2-D or BS2869 1998 Class A1, A2
Injection System	Longkou In-Line "P" Type
Lube Oil Capacity (L)	19
Lube	API CF-4 15W40
Lub. Method	Fully forced pressure feed type
Coolant Capacity (L)	38
Cooling fan	10
Std. Thermostat (Modulating) Range (°C)	82-93
Fan Drive Method	Belt Drive
Cooling Fan Air Flow (m <sup>3</sup> /min)	354
Combustion Air Flow (m <sup>3</sup> /min)	16.3
Maximum Air Intake Restriction (kPa)	3
Exhaust Gas Flow (m <sup>3</sup> /min)	35.9
Max. Back Pressure (kPa)	6
Exhaust Gas Temp (°C)	600
Exhaust Pipe Size (mm)	1 x $\phi$ 84
Start Mode	DC24V Electric Start
Battery	2 x 200 Ah

## ALTERNATOR DATA

Alternator Model	Leroy Somer TAL-A46-D	Rate Power	200/250 kW/kVA
PF.	0.8	Voltage	400/230 V
Phase	3	Frequency	50 Hz.
Connection	3P 4W/Y	Bearing	1
Winding Pitch	2/3	Protection Class	IP23
Insulation Class	H	Efficiency	92.6%
Tel. Influence	TIF < 50	Voltage Regulation	±1%
Harmonic Coefficient	THF < 2%	AVR	R150
Voltage Adjust Scope	≥±5%	Excitation System	SHUNT

### MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,  
 Khwaeng Huai Khwang, Khet Huai Khwang, Bangkok, 10310 Tel. : +66 02 168 3193-5  
 Website : www.multiphase-power.com Line ID : @multiphasepower

## CONTROL SYSTEM DATA (DSE7320)



### Main Feature

The DSE7320 will also monitor the mains (utility) supply. The modules include USB, RS232 and RS485 ports as well as dedicated DSENet® terminals for system expansion.

### Key Function

- 4-Line back-lit LCD text display
- Five key menu navigation
- Front panel editing with PIN protection
- Customisable status screens
- Power save mode
- Support for up to three remote display units
- 9 configurable inputs
- 8 configurable outputs
- Flexible sender inputs
- Configurable timers and alarms
- 3 configurable maintenance alarms
- Multiple date and time scheduler
- Configurable event log (250)
- Integral PLC editor
- Easy access diagnostic page
- CAN and Magnetic Pick-up/Alt. sensing
- Fuel usage monitor and low fuel alarms
- Charge alternator failure alarm
- Manual speed control (on compatible CAN engines)
- Manual fuel pump control
- Power monitoring (kWh, kVAr, kVAh, kVArh)
- Load switching (load shedding and dummy load outputs)
- Automatic load transfer (DSE7320)
- Backed up real time clock
- Start & stop capability via SMS messaging
- USB connectivity
- Tier 4 CAN engine support
- DSENet ® expansion compatible etc.

### MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,  
 Khwaeng Huai Khwang, Khet Huai Khwang, Bangkok, 10310 Tel. : +66 02 168 3193-5  
 Website : www.multiphase-power.com Line ID : @multiphasepower