




**MULTIPHASE
POWER**

Diesel Generator Set

MPY880SC

Powered By SDEC

50 Hz / 1500 RPM



MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,
Khwaeng Huai Khwang, Khet Huai Khwang, Bangkok 10310
Tel. : +66 02 168 3193-5 Fax. : +66 02 168 3192

Email : marketing@multiphase-corp.com Website : www.multiphase-power.com
Facebook : www.facebook.com/MultiphasePower Line ID : @multiphasepower



MPY880SC



MODEL	FREQUENCY / RPM	STANDBY POWER	PRIME POWER
MPY880SC Powered by SDEC	50 Hz/1500 RPM	704 kW	640 kW
		880 kVA	800 kVA


- Available for voltages 400/230V, 480/277V, 380/220V, 440/254V, 416/240V, 220/127V, 208/120V
- All datas based on ISO 3046, altitude 100m (328ft), barometric pressure 100kPa (29.53 inHg), air temperature 25 °C (77 °F), relative humidity 30%.
- Diesel generators comply with standards : ISO8528, ISO14000, ISO3046, GB755, BS5000, VDE0530, IEC34-1
- Model : MPYxxCS – S Suffer for silent type

GENERAL CHARACTERISTICS

Model	MPY880SC
Engine	SDEC 6KTAA25-G31
Alternator	Leroy Somer TAL-A49-C
Voltage (V)	400/230
Current (A)	1155
Connection	3 Phase, 4W/Y
Frequency	50 Hz
Engine Speed (RPM)	1500
Rated Power Factor	0.8
Controller Model	DSE7320

DIMENSIONS

DIMENSIONS	OPEN TYPE	SILENT TYPE
Length (L)	4191 mm	5800 mm
Width (W)	1608 mm	2250 mm
Height (H)	2109 mm	2580 mm
Net Weight (KG)	5400 kg	7050 kg



MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,
Khwaeng Huai Khwang, Khet Huai Khwang, Bangkok, 10310 Tel. : +66 02 168 3193-5
Website : www.multiphase-power.com Line ID : @multiphasepower

STANDARD CONFIGURATION

Engine	SDEC, including air filters, fuel filters, oil filter, starting motor and charging alternator etc.
Alternator	LERROY SOMER brushless AC alternator
Radiator	Silent Type 50 °C (Open Type 40 °C), fan protective shroud
Base Frame	≤ 550 KW : base mounted fuel tank, anti-vibration pads, battery holder > 550 KW : channel steel base frame, anti-vibration pads, battery holder
Circuit Breaker	≤ 63A: Micro Circuit Breaker (MCB) > 63A ≤1250A: Molded case circuit breaker (MCCB), > 1250A: Air circuit breaker (ACB)
Control System	DEEP SEA 7320
Start Battery	Dry charged battery, available for 6 times starts under standard condition; connection cables.
Installation Accessories	Bellow, Elbow and Flange, Exhaust Silencer, etc.
Documents	Electric drawing, Operation & Maintenance Manual, Certification etc.

OPTIONAL CONFIGURATION

Engine Accessories	<ul style="list-style-type: none"> • Heavy-Duty Air Filter • Coolant Heater • Lube Oil Heater • Fuel and Water Separator
Alternator and Accessories	<ul style="list-style-type: none"> • Stamford or Leroy Somer or Others
Cooling System	<ul style="list-style-type: none"> • High Voltage ___ kV • 50 °C Radiator • Heat Exchanger + Water Cooling Tower + External Water Circulation Pumping System • Remote Horizontal Water Tank System
Control System	<ul style="list-style-type: none"> • AMF • Parallel • Practical Type in Low Temperature Environment • Control Screen Heater • Other
Circuit Breaker	<ul style="list-style-type: none"> • ¾ Poles • Fixed/Handcart Type • Electric Mechanism
Automatic Transfer Switch	<ul style="list-style-type: none"> • ATS Cabinet
Start Battery	<ul style="list-style-type: none"> • Nickel-Cadmium Battery • Maintenance-Free Battery • Power Charger and Selector • Charging Current Meter
External Fuel Tank	<ul style="list-style-type: none"> • 500 L, 1000 L, 1500 L, 2000 L, 2500L, 3000L, 4000L, 5000L

MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,
Khwaeng Huai Khwang, Khet Huai Khwang, Bangkok, 10310 Tel. : +66 02 168 3193-5
Website : www.multiphase-power.com Line ID : @multiphasepower



ENGINE DATA

Engine Model	SDEC 6KTAA25-G31
Engine Power	800 kW.
Aspiration	Water-Cooled, Turbo Charged with Aftercool
Displacement (L)	25.18
Type	In-Line
Bore x Stroke (mm)	170 x 185
No. of Cylinders	6
Compression Ratio	14.5 : 1
Governor Type	ECU
Rated Speed (RPM)	1500
Prime Power Fuel Consumption (L/h)	169
Standby Power Fuel Consumption (L/h)	189
Fuel	Sumer: GB 252-2000 top ASTM D975 No.2-D or BS2869 1998 Class A1, A2
Injection System	Electric Type
Lube Oil Capacity (L)	70
Lube	API CF-4 15W40
Max. Temperature (°C)	n/a
Coolant Capacity (L)	200
Max. Top Tank Temp. (°C)	n/a
Std. Thermostat (Modulating) Range (°C)	77-90
Fan Drive Method	Belt Drive
Cooling Fan Air Flow (m ³ /min)	n/a
Combustion Air Flow (m ³ /min)	53.5
Maximum Air Intake Restriction (kPa)	2.5
Exhaust Gas Flow (m ³ /min)	138.9
Max. Back Pressure (kPa)	10
Exhaust Gas Temp (°C)	500
Exhaust Pipe Size (mm)	1 x ϕ 202
Start Mode	DC24V Electric Start
Battery	4 x 200 Ah

ALTERNATOR DATA

Alternator Model	Leroy Somer TAL-A49-C	Rate Power	656/820 kW/kVA
PF.	0.8	Voltage	400/230 V
Phase	3	Frequency	50 Hz.
Connection	3P 4W/Y	Bearing	1
Winding Pitch	2/3	Protection Class	IP23
Insulation Class	H	Efficiency	94.7%
Tel. Influence	TIF < 50	Voltage Regulation	±0.8%
Harmonic Coefficient	THF < 2%	AVR	R150
Voltage Adjust Scope	≥±5%	Excitation System	Shunt

MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,
 Khwaeng Huai Khwang, Khet Huai Khwang, Bangkok, 10310 Tel. : +66 02 168 3193-5
 Website : www.multiphase-power.com Line ID : @multiphasepower

CONTROL SYSTEM DATA (DSE7320)



Main Feature

The DSE7320 will also monitor the mains (utility) supply. The modules include USB, RS232 and RS485 ports as well as dedicated DSENet® terminals for system expansion.

Key Function

- 4-Line back-lit LCD text display
- Five key menu navigation
- Front panel editing with PIN protection
- Customisable status screens
- Power save mode
- Support for up to three remote display units
- 9 configurable inputs
- 8 configurable outputs
- Flexible sender inputs
- Configurable timers and alarms
- 3 configurable maintenance alarms
- Multiple date and time scheduler
- Configurable event log (250)
- Integral PLC editor
- Easy access diagnostic page
- CAN and Magnetic Pick-up/Alt. sensing
- Fuel usage monitor and low fuel alarms
- Charge alternator failure alarm
- Manual speed control (on compatible CAN engines)
- Manual fuel pump control
- Power monitoring (kWh, kVAr, kVAh, kVArh)
- Load switching (load shedding and dummy load outputs)
- Automatic load transfer (DSE7320)
- Backed up real time clock
- Start & stop capability via SMS messaging
- USB connectivity
- Tier 4 CAN engine support
- DSENet ® expansion compatible etc.

MULTIPHASE CORPORATION CO., LTD.

90 CW Tower, Room No.A2102, 21st Floor, Ratchadapisek Road,
 Khwaeng Huai Khwang, Khet Huai Khwang, Bangkok, 10310 Tel. : +66 02 168 3193-5
 Website : www.multiphase-power.com Line ID : @multiphasepower